

LAMP83

A thick red horizontal bar that spans the width of the text 'LAMP83' and extends slightly beyond its right edge.

2023

2025

Adını görünümünden alan RING serisi, sıva üstü ve sarkıt modelleri ile dekoratif bir tasarıma sahip olup yüksek performans ve fonksiyonel çözümler sunuyor.

Özel pleksi sayesinde kamaşma etkisi minimuma indirilerek saf ve homojen bir ışık elde edilmesi mümkündür. 300 cm'e kadar sarkıtılabilen versiyonları sayesinde yüksek tavan uygulamalarında dahi sorun yaşanmıyor.

Kullanım Alanları:

Farklı ebatlarda ürünler içeren RING ailesi, genel aydınlatmaya ihtiyaç duyulan evler, ofisler, bankalar, mağazalar, marketler, ticari alanlar, alışveriş merkezleri vb. mekânların aydınlatılmasında kullanılabilir.

Taking its name from its appearance, RING series has a decorative design with its surface mounted and pendant models and offers high performance and functional solutions.

Thanks to special plexy, glare effect is reduced to minimum and it is possible to get a pure and homogeneous light. Thanks to pendant versions being able to hang up to 300 cm, there is no problem even in high ceiling applications.

Application Areas:

RING family, including different sized products, can be used to illuminate places like homes, offices, banks, shops, markets, trading areas shopping malls etc. where general lighting is needed in round form.



RING







RING


İŞ BANKASI - İSTANBUL GİRİŞİMCİLİK ŞUBESİ





RING

TEB BUDOTEK OFİS - İSTANBUL



RING

ÜRÜN AİLESİ / *PRODUCT FAMILY*

RING SIVA ÜSTÜ / SURFACE MOUNTED



RING SARKIT / PENDANT



- Sıva üstü ve sarkıt gövde seçenekleri
- 40 - 80 - 100 cm çap
- L 80 50.000 saat ömürlü LED
- 2.900 - 4.100 lümen arası (LED) ışık akısı
- 3000K - 4000K (CCT) ışık renk sıcaklığı
- DALI dim seçeneği, otomasyona uyumlu (opsiyonel)
- Opal difüzör ve Mikroprizmatik difüzörle düşük kamaşma ($UGR \leq 19$)
- İnsan Odaklı Aydınlatma®
- Tunable White (2700K - 6500K) seçeneği
- 3 saat süreli acil durum batarya kiti (opsiyonel)


- Surface mounted and pendant body options
- 40 - 80 - 100 cm as diameter
- 50.000 hours life time LED
- LED lumen output between 2.900 - 4.100 lm
- 3000K - 4000K (CCT) light color temperature
- DALI dim option, suitable for automation (optional)
- Opal diffuser and Low glare effect with microprismatic diffuser ($UGR \leq 19$)
- Human Centric Lighting®
- Tunable White (2700K - 6500K) option
- Emergency kit is available with 3-hours battery pack (optional)

RING SIVA ÜSTÜ / SURFACE MOUNTED



W • lm	Standard	DALI Dimm	Ø (mm)
25 W • 1915 lm	L SU2321030	L SU2321040	600
35 W • 2681 lm	L SU2322030	L SU2322040	800
45 W • 3447 lm	L SU2323030	L SU2323040	1000

W • lm	UGR<19	UGR<19 DALI	Ø (mm)
25 W • 1915 lm	L SU2321130	L SU2321140	600
35 W • 2681 lm	L SU2322130	L SU2322140	800
45 W • 3447 lm	L SU2323130	L SU2323140	1000



C + T + E



3000K - 4000K • 3500 - 9000 gr

CE IP 20 850°



RING

TEB BUDOTEK OFİS - İSTANBUL

Ürünleri, tabloda belirtilen versiyonlarla almak istiyorsanız, ürün kodunun sonuna ilgili harfi ekledikten sonra Lamp 83 müşteri temsilciniz ile temasa geçebilirsiniz.
If you would like to buy the products featuring options given in the table, please add relevant letter code to the end of product code and consult your Lamp 83 customer representative.

C Casambi kontrol
Casambi control

T Tunable white - 2700K~6500K
Tunable white - 2700K~6500K

E Acil kit - 3 saat
Emergency kit - 3 hours

W Ahşap renkli
Wooden color


Ürünlerimizle ilgili daha detaylı teknik bilgileri ve ışık eğrilerini www.lamp83.com.tr web sitemizde bulabilirsiniz. / Please visit www.lamp83.com.tr for further technical information and light distribution datas.

RING SARKIT / PENDANT



W • lm	Standard	DALI Dimm	Ø (mm)
25 W • 1915 lm	L SK2321030	L SK2321040	600
35 W • 2681 lm	L SK2322030	L SK2322040	800
45 W • 3447 lm	L SK2323030	L SK2323040	1000

W • lm	UGR<19	UGR<19 DALI	Ø (mm)
25 W • 1915 lm	L SK2321130	L SK2321140	600
35 W • 2681 lm	L SK2322130	L SK2322140	800
45 W • 3447 lm	L SK2323130	L SK2323140	1000



C + T + E



3000K - 4000K • 3500 - 9000 gr

CE IP 20 850°

Ürünleri, tabloda belirtilen versiyonlarla almak istiyorsanız, ürün kodunun sonuna ilgili harfi ekledikten sonra Lamp 83 müşteri temsilciniz ile temasa geçebilirsiniz.
If you would like to buy the products featuring options given in the table, please add relevant letter code to the end of product code and consult your Lamp 83 customer representative.

C Casambi kontrol
Casambi control

T Tunable white - 2700K~6500K
Tunable white - 2700K~6500K

E Acil kit - 3 saat
Emergency kit - 3 hours

W Ahşap renkli
Wooden color

Ürünlerimizle ilgili daha detaylı teknik bilgileri ve ışık eğrilerini www.lamp83.com.tr web sitemizde bulabilirsiniz. / Please visit www.lamp83.com.tr for further technical information and light distribution datas.